Artist NAIL DESIGN

Safety Data Sheet

Section 1: Identification of the	he Substance/Preparation and of the Company/U	ndertaking				
Product Name:	Artistic Putty Polygel - Shaping Liquid	SDS Prepared:	6/8/2017			
Chemical Name:	N/A	SDS Modified:	3/16/2020			
		Revision	01			
Family:	Nail Liquid	Supplied by:	Nail Alliance	 North America, Inc 		
Product Use:	Nail Enhancement		1545 Moonst	one		
			Brea, CA 928	321		
		Emergency Phor	ne Number:	(800) 535-5053		
Product Item#:	2840000, 2840001	Information Con	tacts:	(714) 773-9758		
Section 2: Hazards Identifica	ition					
	GHS Labeling - Hazard Picto	ograms				
Signal Word:	Danger					
Hazard Statements:	H225 - Highly flammable liquid and vapor					
	H319 - Causes serious eye irritation					
	H335 - May cause respiratory irritation					
	H402 - Harmful to aquatic life					
Precautionary statements	P210 - Keep away from heat, hot surfaces, open flames, sp	arks No smoking				
	P233 - Keep container tightly closed					
	P243 - Take precautionary measures against static discharge					
	P261 - Avoid breathing mist, vapors, spray P264 - Wash exposed skin thoroughly after handling					
	P271 - Use only outdoors or in a well-ventilated area					
	P305+P351+P338 - If in eyes: Rinse cautiously with water for	or several minutes. Remove	contact lenses,	if present and easy to do.		
	Continue rinsing					
	P312 - Call a POISON CENTER or doctor/physician if you for P337+P313 - If eye irritation persists: Get medical advice/at					
	P370+P378 - In case of fire: Use dry chemical powder, alco		ioxide			
	(CO2) to extinguish					
	P403+P233 - Store in a well-ventilated place. Keep containe	er tightly closed				
	P405 - Store locked up P501 - Dispose of contents/container to comply with local, s	state and federal regulations				
	· · · · · · · · · · · · · · · · · · ·					
	P235 - Keep cool					
	P235 - Keep cool If inhaled: Remove person to fresh air and keep comfortable	e for breathing				
Potential Health Effects. Sign	If inhaled: Remove person to fresh air and keep comfortable	e for breathing				
	If inhaled: Remove person to fresh air and keep comfortable	e for breathing				
Primary Route of Entry	If inhaled: Remove person to fresh air and keep comfortable as & Symptoms of Exposure: Inhalation, skin and ingestion Vapors are irritating to the eyes. Splashes may cause sever		ıring, redness, a	ind pain with possible corneal		
Potential Health Effects, Sigr Primary Route of Entry Eye	If inhaled: Remove person to fresh air and keep comfortable is & Symptoms of Exposure: Inhalation, skin and ingestion Vapors are irritating to the eyes. Splashes may cause seven damage.	re irritation, with stinging, tea	<u>.</u>			
Primary Route of Entry Eye	If inhaled: Remove person to fresh air and keep comfortable as & Symptoms of Exposure: Inhalation, skin and ingestion Vapors are irritating to the eyes. Splashes may cause seven damage. Repeated/prolonged contact may cause drying of the skin.	re irritation, with stinging, tea Symptoms include redness,	burning, drying,	cracking and skin burns.		
Primary Route of Entry	If inhaled: Remove person to fresh air and keep comfortable is & Symptoms of Exposure: Inhalation, skin and ingestion Vapors are irritating to the eyes. Splashes may cause seven damage.	re irritation, with stinging, tea Symptoms include redness, ely to cause harmful effects;	burning, drying,	cracking and skin burns.		
Primary Route of Entry Eye Skin	If inhaled: Remove person to fresh air and keep comfortable is & Symptoms of Exposure: Inhalation, skin and ingestion Vapors are irritating to the eyes. Splashes may cause seven damage. Repeated/prolonged contact may cause drying of the skin. S Swallowing small amounts during normal handling is not like	re irritation, with stinging, tea Symptoms include redness, ely to cause harmful effects; g.	burning, drying, swallowing larg	cracking and skin burns. Je amounts may be harmful. This		

NOTE: Refer to Section 11, Toxicological Information for Details

Section 2: Hazardous Ingredients

INCI Name	CAS #	EINECS#	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IAR/NTP/OSHA	%
Isopropyl Alcohol	67-63-0	200-661-7	400 ppm/980	200/400 ppm	Not Listed	50.0 - 65.0
Isobutyl Acetate	110-19-0	203-745-1	150 ppm (700 mg/m3)	150 ppm	Not Listed	20.0 - 30.0
Acetone	67-64-1	200-662-2	N/E	N/E	Not Listed	5.0 - 20.0

Section 4: First Aid Measures

First Aid for Eye	Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.
First Aid for Skin	Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists.
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the lieftside with head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.
First Aid for Inhalation	Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Seek medical attention if discomfort persists.

Section 5: Fire Fighting Measures

Flash Point (est.) (°F/°C)		Flammable Limit	Auto-Ignition Temperature	
		(vol%)	(vol%)	
1° F/ -17 ° C		LEL: 2%; UEL: 11.4%	N/DA	
Extinguishing Media:	Alcohol resisant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth maybe used for small fires only			
Fire Fighting Instructions:	If potential for exposure to vapors or products of combustion, wear complete personal protective equipment including self contained breathering apparatus, with full face operated in pressure demand. Fight fire from a safe distance/protected location. Water spray will reduce the intensity of flames			
All storage areas should be provided with adequate fire fighting facilities. Keep adjacent containers cool by spraying with water Inusual Hazards: expose containers shoud be cooled with water to prevent pressure build up		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		

Section 6: Accidental Release Measures

Spill or Release Procedures:	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unneccesary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (eg. vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush or sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. Liquids/vapors may ignite.
Section 7: Handling and S	Storage
Handling	Closed containers exposed to temperature above (120°F) in transist or storage may develop vapor pressure. Open containers slowley. Ground all metals containers when transfering material. Wash face and hands thoroughly with soap and water after handling and before eating, drinking or smoking. Keep away from the heat, sparks & open flames. Do not smoke. Avoid sparks
Storage	Store in a cool, well vetilated area away from heat, sparks and flame. Keep containers closed when not in use.
Evelopies Henry	Elammable liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

Explosion Hazard Flammable liquid. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Section 8: Exposure Controls/Personal Protective Equipment

Engineering Controls	Facilities storing or utilizing this material should be equipped with an eye facitily and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
Personal Protective Equipment:	
General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/Face Protection	Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type of face shield.
Skin Protection	Use impermeable clothing to prevent ANY contact with this product, such as chemical resistant gloves, apron, boots, or whole body suit. Neoprene and Nitrile rubber is better than PVC.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is

circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN149 approved full-facepeice airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149.

Section 9: Physical and Chemical Properties Odor & Odor Threshold Appearance voc (g/L) Specific Gravity Viscosity % Volatile Clear, blue, mobile liquid 632 (H2O =1):0.82 N/A W/W % : 99+ Pungent mix odor Octanol/Water Vapor Igniti itioning Coeffic Log Po/w Material VOC Vapor Density Solubility In Water (20°C) **Boiling Point/ Freezing Point** Pressur Evaporation Rate on e: 73 mm Slower than 632 g/l N/DA Hg @ 133 °C Heavier than air N/A Miscible ether 20°C Auto-Ignition Temperature Flash Point Flammable Limit Page 2 of 7 Artistic Putty PolyGel - Shaping Liquid

(°F/°C)		(vol%)	(vol%	1%)	
1 °F/-17 °C (est)		LEL:2% ; UEL:11.4%	N/DA		
Section 10: Stability and Reactiv	vity				
Stability: Stable Hazardous Decomposition Products: Carbon Monoxide		Incompatibility (Materials to Avoid): Oxidizing agents, i.e. hydrogen peroxide, Nitric Acid, Perchloric Acid, Perchloric Acid, Chromium Trioxide Hazardous Polymerization: Will not occur			
Conditions to Avoid: leat, flames, ignition sources, and incomp	ns to Avoid:				
Section 11: Toxicological Inform	nation				
Acute Oral Toxicity	Acute Dermal Toxicity	cute Inhilation Toxicit	Irritation - Skin	Irritation - Eye	
N/DA	N/DA	N/DA	N/DA	N/DA	
Sensitization		Mutagenicity	Sub-chronic Toxicity		
N/DA		N/DA	N/DA		
Section 12: Ecological Informati	on				
Ecotoxicological Information:					
Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria	
N/DA	N/ DA	N/ DA	N/ DA	N/ DA	
Chemical Fate Information					
Biodegradability		into the soil, this materia material may biodegrad evaporate. When releas and 10 days. When rele	soil, this material is expected to quic al may leach into groundwater. When le extent. When released to water, thi sed into water, this material is expect eased into water, this material may bid ected to significantly bioaccumulate.	n released into the soil, this s material is expected to quick and to have a half-life between	

Section 13: Disposable Considerations

Dispose of diking materials and absorbent in compliance with State, Local and Federal regulations. Residual vapors may explode on ignition, do not cut, drill or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14: Transport Information

DOT (49 CFR 172)

Consumer Commodity, ORM-D (</= 1.0L) UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II (>1.0L)

IATA (DGR):

Consumer Commodity, 9, ID8000 (</= 0.5L) UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II (>0.5L)

IMO (IMDG):

Consumer Commodity, ORM-D (</= 1.0L) UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II (>1.0L)

TDGR (Canadian GND):

Mark Package "Limited Quanitty" or "Quantitie Limitee" or "LTD QTY" or "Quant Ltee" (</=1.0L) UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II (>1.0L)

ADR/RID (EU):

UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II, ADR, LTD QTY (</=1.0L)

Mexico (SCT):

UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II, Cantidad Limitada (</=1.0L)

ADGR (AUS):

UN1993 Flammable Liquid n.o.s. (Isopropyl Alcohol, Isobutyl Acetate), 3, II

Section 15: Regulatory Information

US Federal Regulations

ee i eacial hegalaliene	
Clean Air Act: HAP/ODS This product contains the following (HAP's): or 0DS:	
	• NONE
Clean Water Act: Priority Pollutant	The following ingredients are listed as hazardous pollutants under the CWA:

None of the ingredients are listed as primary pollutants nor are they listed as toxic pollutants.

FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food-packaging additive.
	This product is considered to be hazardous under the OSA Hazard Communication Standard. Its hazards are:
Occupational Safety and Health Act	Immediate (acute) health hazard
	Fire hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261):
RORA	Characteristic of Ignitability, RCRA Code: D001
SARA Title III: Section 302	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA title III: Section 304	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List):
	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are:
SARA Titile III: Section 311-312:	Immediate (acute) health hazard
	Fire hazard

	This product contains the following chemicals which are subject to the reporting requirements of Section 313 Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:		
SARA Title III: Section 313:	Isopropyl Alcohol CAS# 67-63-0 70%		
TSCA Section 8(b): Inventory	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.		

State Regulations

CA Right-to Know- Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
California No Significant Risk Rule:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
MA Right-to-Know Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
NJ Right-to-Know Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
PA Right-to-Know Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
FL Right-to-Know Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
MN Right-to-Know Law:		Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	
International Regualations			
CDSL: Canadian Inventory Transitional List)	(on Canadian	Isopropyl Alcohol CAS # 67-63-0; Ethyl Acetate CAS #141-78-6-Acetone CAS# 67-64-1	

Labeling according to EC Directives - 1999/45/EC

European Community:		
		HAZARD SYMBOLS: Xn, F: Highly Flammable
	JHL .	 RISK PHRASES: R11: highly flammable, R20/22: Harmful by inhalation and if swallowed, R36/37/38: Irritating to eyes, respiratory system and skin
\checkmark		S16: keep away from sources of ignition-no smoking, S24/25: avoid contact with skin and eyes, S33: take precautionary measures against static discharges, S37/39: wear suitable gloves and eye/face protection, S45: In case of accident or if you feel unwell, seek medical

Section 16: Other Information

(1)

EU Classes and Risk / Safety Phrases for Referenced ingredients (See Section 2): F: Flammable substance or preparations	
Risks Phrases:	
R11: Highly Flammable	
R36: Irritating to eyes	
R66: Repeated exposure may cause skin dryness or cracking	
R67: Vapours may cause drowsiness and dizziness	
Safety Phrases:	
S2: Keep out of the reach of children	
S7: Keep container tightly closed	
S9: Keep container in a well-ventilated place	
S16: Keep away from sources of ignition - No smoking	
S24/25: Avoid contact with skin and eyes	
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
S23: Do not breathe gas/fumes/vapour/spray	
S29: Do not empty into drains	
S33: Take precautionary measures against static discharges	
Hazard Rating System (Pictograms)	
NFPA: HMIS:	
flammability (3)	1 HEALTH
Blue Yellow	

(0)

White special

•

PERSONAL PROTECTION

Revised Sections Since Last Verion:

NONE

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or exprense arising out of any way connected with the handling, storage, use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If one could have any concerns with or problems understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Systems at 1(800) 535-5053.