SAFETY DATA SHEET PREMIUM ACID FREE PRIMER

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name: Use of substance / mixture:	Premium Acid Free Primer Nail Primer PC 39: Cosmetics, personal care products.
Details of the supplier of the safety Company name: Tel: Fax: Email:	International Beauty Partners B.V. De Run 4221 5503 LM Veldhoven The Netherlands +31 (0) 40 - 2069509 +31 (0) 40 - 2065481
Emergency tel:	+31 (0) 40 - 2069509 (office hours only)

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification under CHIP	F+: R12; Xi: R36; -: R66; -: R67
Classification under CLP	STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 1: H224
Most important adverse effects	Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or
	cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP	
Hazard statements	H224: Extremely flammable liquid and vapour.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
Signal words	Danger
Hazard pictograms	GHS02: Flame GHS07: Exclamation mark

Precautionary statements	 P280: Wear. P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTER or doctor if you feel unwell. P370+378: In case of fire: Use for extinction. 	
Label elements under CHIP		
Hazard symbols	Extremly flammable. Irritant.	
Risk phrases	R12: Extremely flammable. R36: Irritating to eyes. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.	
Safety phrases	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	

2.3 Other hazards

Other hazards	In use, may from flammable/explosive vapour-air mixture.
PBT	This substance is not identified as a PBT substance.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Hazardous Ingredients ETHYL ACETATE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
205-500-4	141-78-6	[F] R11; [Xi] R36; [-] R66; [-] R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	>75%

ACETONE

200-662-2	67-64-1	[F] R11; [Xi] R36; [-] R66; [-] R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-5%
			STOT SE 3: H336; -: EUH066	

ACRYLIC ESTER

-	29570-58-9	Xi: R36	-	1-5%
---	------------	---------	---	------

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Skin contact	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.	
Eye contact	Bathe the eye with running water for 15 minutes. Consult a doctor.	
Ingestion	Wash out mouth with water. Consult a doctor.	
Inhalation	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.	

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	There may be irritation and redness at the site of contact	
Eye contact	There may be irritation and redness. The eyes may water profusely.	
Ingestion	There may be soreness and redness of the mouth and throat.	
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.	
Delayed / immediate effects	Immediate effects can be expected after short-term exposure.	

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment	Eye bathing equipment should be available on the premises.
-------------------------------	--

SECTION 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Extinguishing Media	Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water
	spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards	Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
-	Vapour may travel considerable distance to source of ignition and flash back.

5.3 Advice for fire-fighters

Advice for fire-fighters	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with
	skin and eyes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Refer to section 8 of SDS for personal protection details. If outside do not approach from
_	downwind. If outside keep bystanders upwind and away from danger point. Mark out the
	contaminated area with signs and prevent access to unauthorized personnel. Turn leaking
	containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which
	may produce sparks.

6.4. Reference to other sections

Reference to other sections	Refer to section 8 of SDS.
-----------------------------	----------------------------

SECTION 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling requirements	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
	Do not handle in a confined space. Avoid the formation or spread of mists in the air.
	Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in cool, well ventilated area. Keep away from sources of ignition. Keep container
_	tightly closed. Prevent the build up of electrostatic charge in the immediate area. Ensure
	lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s) No data available.	
--	--

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Hazardous ingredients

ETHYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	200 ppm	400 ppm	-	-

ACETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

8.2. DNEL/PNEC Values

DNEL/PNEC No data available.		
	DNEL/PNEC	No data available.

8.3. Exposure controls

Engineering measures	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.	
Respiratory protection	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection	Protective gloves.	
Eye protection	Safety glasses. Ensure eye bath is to hand.	
Skin protection	Protective clothing.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Colourless
Odor	Characteristic odor
Evaporation rate	Fast
Viscosity	Non-viscous
Flash point°C	-4

9.2. Other information

Other information	No data available.
-------------------	--------------------

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

	Stable under recommended transport or storage conditions.	
10.2. Chemical stability		
	Ctable under normal conditions. Ctable at room term enture	
Chemical stability	Stable under normal conditions. Stable at room temperature.	
10.3. Possibility of hazardous rea	ctions	
Hazardous reactions	Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.	
10.4. Conditions to avoid		
Conditions to avoid	Heat. Hot surface. Source of ignition. Flames.	
10.5. Incompatible materials		
Materials to avoid	Strong oxidizing agents. Strong acids.	
10.6. Hazardous decomposition p	roducts	
Hazardous decomposition produc	ts In combustion emits toxic fumes.	

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Hazardous ingredients

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

Relevant effects for mixture

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Compilation date : 23-01-2009 revision; 1

Skin contact	There may be irritation and redness at the site of contact.	
Eye contact	There may be irritation and redness. The eyes may water profusely.	
Ingestion	There may be soreness or redness of the mouth and throat.	
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.	
	Exposure may cause coughing or wheezing.	
Delayed / immediate effects	Immediate effects can be expected after short-term exposure.	

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

	N 1
Ecotoxicity values.	No data available.
12.2. Persistence and degradability	
Persistence and degradability	Biodegradable.
12.3. Bioaccumulative potential	
Bioaccumulative potential	No bioaccumulation potential.
12.4. Mobility in soil	
Mobility:	Readily absorbed into soil.
12.5. Results of PBT and vPvB assessment	
PBT identification	This product is not identified as a PBT substance.
12.6. Other adverse effects	
Other adverse effects	Negligible exotoxicity.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal operations	Transfer to a suitable container and arrange for collection by specialised disposal company.
NB	The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

Compilation date : 23-01-2009 revision; 1

UN number	UN1993

14.2. UN proper shipping name

Shipping name	ne FLAMMABLE LIQUID, N.O.S.	
	(ETHYL ACETATE, ACETONE, DHPA MIXTURE	

14.3. Transport hazard class(es)

Transport class 3		
	Transport class	3

14.4. Packing group

Packing group	I

14.5. Environmental hazards

Environmentally hazardous	No
Marine pollutant	No

14.6. Special precautions for user

Special precautions No special precautions.	
---	--

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

SECTION 16. OTHER INFORMATION

Other information:

Other information	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3	EUH066: Repeated exposure may cause skin dryness or cracking.
	H224: Extremely flammable liquid and vapour.
	H225: Highly flammable liquid and vapour.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	R11: Highly flammable.
	R12: Extremely flammable.
	R36: Irritating to eyes.
	R66: Repeated exposure may cause skin dryness or cracking.
	R67: Vapours may cause drowsiness and dizziness.
Legal disclaimer	The above information is believed to be correct but does not purport to be all inclusive
_	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.