Material Safety Data Sheet

Regulation (EC) No. 1907/2006, 1272/2008 Version No.: 1.0 Printing Date: July 1, 2021 Page 1/1

MSDS REPORT

GW Investments B.V. Olen 26, 5474 Nuenen The Netherlands

SDS Report No : SDS202106300005-1

Compilation Date : 30-06-2021

Trade Name : NailPerfect Color + Gel (Gels)

Product Names: NailPerfect Color + Gel Black

NailPerfect Color + Gel White
NailPerfect Color + Gel Red
NailPerfect Color + Gel Blue
NailPerfect Color + Gel Yellow
NailPerfect Color + Gel French Gel
NailPerfect Color + Gel Foil Design Gel

Compasition of the Ingredients: See section 3 on the SDS

Service Requested: Safety Data Sheet (SDS) for the requested sample.

Summary : The contents and the formats of the MSDS are prepared in

accordance with Regulation EC No 1907/2006, 1272/2008 Regulation (EU) No 2015/830 and are provided per atta-

ched.

SECTION 1: Identification of the Substance/Mixture and of the Company

1.1 Product Identifier

Trade Name: NailPerfect Color + Gel (family/product range)

The family range of products have the same basic ingredients, with variation in color-additives.

Packaging in 7 gr and 14 gr.

Registration number: Data not available Made in: GERMANY (European Union)

1.2 Relevant identified uses of the substance or mixture and uses advised against on Application of the substance/misture: Nail Art, Manicure, Pedicure, Nailcare

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GW Beauty B.V.

Olen 26, 5474 Nuenen

The Netherlands

Tel: +31 617648788

Email: info@gwinvestments.nl

Further information obtainable from: GW Investments B.V.

1.4 Emergency telephone number

EU and Russia: 112 (Available 24 hours per day) UK: 999 (Available 24 hours per day)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to regulation (EC) 1272/2008:

Classification under CLP	Skin Irrit. 2: H315 Causes skin irritation; Skin Sens. 1: H317 May cause allergic skin reactions; Eye Irrit. 2: H319 Causes serious eye irritation
Most important adverse effects	Irritating to eyes. Causes serious eye irritation. May cause an allergic reaction. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2 Label Elements

Label elements under CLP	
Hazard statements	H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.
Signal words	WARNING
Hazard pictograms	GHS07: Exclamation mark
Precautionary statements	P280: Wear: Protective clothing, Eye protection, protective mask, faceprotection, gloves. P302+352: IF ON SKIN: Wash with plenty of water/soap. P332 + P313: If skin irritation or rash occurs: Get medical advice / attention. P305 + P352 + P338 - IF IN EYES: Rinse cautiously with water for several minutes Rinse. Remove any contact lenses if possible. Continue rinsing. P337 + P313: If eye irritation persists: Get medical advice / attention.
Label elements under CHIP	Irritant.
Hazard symbols	
Risk phrases	R36: Irritating to eyes.
Cont. Risk Phrases	R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.

Safety phrases	S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
Signal words	WARNING

2.3 Other Hazards

Other hazards	Excessive inhalation of vapors may irritate the respiratory system.
PBT	This substance is not identified as a PBT substance.
Signal words	WARNING

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

Hazardous ingredients:

INCI NAME	Aliphatic Urethane	Δcrylate		
	Aliphatic Orethane	Aciyiale		
Mol. Formula	-			
REACH Number	Not Listed			
Cosmetic Function	FLEXIBLE BINDER	3		
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
934-754-5	-	Aliphatic urethane	Acute Tox. 4: H302;	
		acrylate	Acute Tox. 4: H312;	
			Acute Tox. 4: H332;	
			Skin Irrit. 2: H315;	
			Eye Irrit. 2 : H319.	

Aliphatic Urethane Diacrylate

Mol. Formula

INCI NAME	Aliphatic Urethane	Di-crylate		
Mol. Formula	-			
REACH Number	Not Listed			
Cosmetic Function	FLEXIBLE BINDER	₹		
EC Number	CAS Number	Chemical ID	CLP Classification	Percent
-	-	-	-	

NAILPERFECT

PROFESSIONAL SYSTEMS

INCI NAME	Ethylphenyl(2,4,6-t	rimethylbenzoyl)pho	osphinate	
Mol. Formula	C ₁₈ H ₂₁ O ₃ P			
REACH Number	Not REACH registe	Not REACH registered		
Cosmetic Function	PHOTO INITIATIN	G		
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
282-810-6	84434-11-7	Ethyl phenyl(2,4,-6-trimethylben-zoyl)phosphinate	Aq. Acute 1: H400; Aq. Chron. 2: H411; Skin Sens. 1B: H317; STOT SE 1: H370; STOT RE2: H373; STOT SE 3: H335; Carc. 1A: H350; Aq Chron 2: H411; Aq Chron 3: H412; Aq Chron 4: H413; Repr. 2: H361.	

INCI NAME	Polyethylene glyco	l200dimethacrylate		
Mol. Formula	C20H32N2O8			
REACH Number	Index No: 604-044 EC Regulation Pro			
Cosmetic Function	BINDING			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
607-819-8	25852-47-5	2-(2-methylprop- -2-enoyloxy)ethyl 2-methylprop- -2-enoate	Skin Sens. 1: H317; Skin Sens. 2: H315; Eye Irrit. 2: H319; STOT SE 3: H335; Aq. Chron. 3: H412; Skin Irrit. 2: H315.	

INCI NAME	SILICA DIMETHYL	SILYLATE		
Mol. Formula	C ₂ H ₆ Cl ₂ Si.O ₂ Si			
REACH Number	Not Listed			
Cosmetic Function	VISCOSITY CONT	ROL / ANTI-CRAC	KING	
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
271-893-4	68611-44-9	Silane, dichlorodi- methyl-, reaction products with silica	Acute Tox. 2: H330; Acute Tox. 1: H330; STOT RE 2L: H373; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335.	

NAILPERFECT

PROFESSIONAL SYSTEMS

INCI NAME	ISOPROPYLIDENI TE	EDIPHENYL BISOX	YHYDROXYPROPYL N	METHACRYLA-
Mol. Formula	C29H36O8			
REACH Number	Not Listed			
Cosmetic Function	FILM FORMING			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
216-367-7	1565-94-2	(1-methy- lethylidene) bis[4,1-phenyle- neoxy(2-hydroxy- -3,1-propanediyl)] bismethacrylate	Eye Dam. 1: H318; Skin Sens. 1: H317; Skin Irr. 2: H315; Eye Irr. 2: H319; Aq. Chron. 3: H412; STOT SE 3: H335; Acute Tox. 4: H302; Skin Corr. 1C: H314; Matu. 2: H341.	

INCI NAME	CI 45410			
Mol. Formula	C20H4Br4Cl4O5.2Na	•		
REACH Number	Not Listed			
Cosmetic Function	COLORANT			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
242-355-6	18472-87-2	3,4,5,6-te-	Skin Irrit. 2: H315;	
		trachloro-	Eye Irrit. 2: H319;	
		-2-(1,4,5,8-tetra-	STOT RE 2: H373;	
		bromo-6-hydroxy-	STOT SE 3: H335;	
		-3-oxoxanthen-	Aq. Acute 1: H400;	
		-9-yl)benzoic acid	Aq. Chron 2: H411;	
			Aq. Chron 3: H412.	

INCI NAME	Ethylhexyl Acrylate			
Mol. Formula	C ₁₁ H ₂₀ O ₂			
REACH Number	Index No: 607-107-	-00-7		
Cosmetic Function	BINDING			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent

NAILPERFECT PROFESSIONAL SYSTEMS

INCI NAME	BHT			
Mol. Formula	C40H22Cl6N6O4			
REACH Number	Not Listed			
Cosmetic Function	ANTIOXIDANT			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
204-881-4	128-37-0	2,6-di-tert-butyl-p- -cresol	Aq. Chron. 1: H410; Aq. Acute: 1; H400; Aq. Chron. 4: H413; Acute Tox. 4: H302; Acute Tox. 4: H312; Acute Tox. 4: H332; STOT SE 3: H335;	
			Skin Irrit. 2: 315; Eye Irrit. 2: H319; STOT RE 2: H373; Muta. 1B: H340; Carc. 2: H351; Repr.2 : H361.	

INCI NAME	P-HYDROXYANISOLE			
Mol. Formula	C7H8O2	C7H8O2		
REACH Number		Index No: 604-044-00-7 EC Regulation Provision: III/95		
Cosmetic Function	REDUCING			
EC Number	CAS Number	Chemical ID	CLP Classification	Percent
205-769-8	150-76-5	Mequinol	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Sens. 1:H317; Aq. Chron. 3: H412; Acute Tox. 4: H302; Repr. 2: H361.	

 $\mathsf{T}\mathsf{N}$

NAILPERFECT

PROFESSIONAL SYSTEMS

INCI NAME	Hydroquinone			
Mol. Formula	C ₆ H ₆ O ₂	$C_6H_6O_2$		
REACH Number	Index No. 604-005			
	(EC) 2013/344 An	nex III/14		
Cosmetic Function	REDUCING			
EC Number	CAS Number	Chemical ID	CLP Classification	Percent
204-617-8	123-31	Hydroquino- ne	Carc. 2: H351; Muta. 2: H341; Acute Tox. 4 *: H302; Eye Dam. 1: H318; Skin Sens. 1:H317; Aq. Acute 1: H400. Professional Use Only.	

INCI NAME	CI 77499			
Mol. Formula	Fe ₃ O ₄ (FeO·Fe ₂ O ₃)	Fe ₃ O ₄ (FeO·Fe ₂ O ₃)		
REACH Number	Not Listed	Not Listed		
Cosmetic Function	COLORANT			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
235-442-5	12227-89-3	Iron oxide black	Acute Tox. 4: H332; Self-heat. 1: H251; Self-heat. 2: H252.	

INCI NAME	CI 74160			
Mol. Formula	C32H16CuN8			
REACH Number	Not Listed			
Cosmetic Function	COLORANT			
EC Number	CAS Number	Chemical ID	Not class. but may exp.	Percent
205-685-1	147-14-8	29H,31H-phtha- locyaninato(2-) 29,N30,N31,N32 copper	Skin Sens. 1: H317; Aq. Chron. 4: H413; Aq. Chron. 3: H412; Aq. Acute 1: H400; Aq. Chron. 1: H410; Expl. 1.6: H317; Expl. 1.6: H413; Skin Irrit. 2; H315; Eye Irrit. 2: H319.	

4.2 Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs

or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

TN

NAILPERFECT PROFESSIONAL SYSTEMS

	1
Ingestion	Wash out mouth with water.
	Remove dentures if any.
	Remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
	If material has been swallowed and the expo-
	sed person is conscious, give small quantities
	of water to drink.
	Stop if the exposed person feels sick as vomi-
	ting may be dangerous.
	Do not induce vomiting unless directed to do so
	by medical personnel.
	If vomiting occurs, the head should be kept low
	so that vomit does not enter the lungs.
	Get medical attention if adverse health effects
	persist or are severe.
	Never give anything by mouth to an uncons-
	cious person. If unconscious, place in recovery
	position and get medical attention immediately.
	Maintain an open airway.
	Loosen tight clothing such as a collar, tie, belt
	or waistband.
Protection of first-aiders	No action shall be taken involving any personal
	risk or without suitable training.
	It may be dangerous to the person providing
	aid to give mouth-to-mouth resuscitation.
	Wash contaminated clothing thoroughly with
	water before removing it, or wear
	gloves.
	1 -

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	There may be irritation and redness at the site of contact.
Eye Contact	There may be irritation and redness. The eyes may water profusely.
Ingestion	There may be soreness and redness of the mouth and throat.
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.
Delayed/ Immediate Effects	Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

ĺ	Immediate special treatment	Eye bathing equipment should be available on
	miniculate special treatment	Lyc battling equipment should be available on
		the premises.

4.4. Most important symptoms and effects, both acute and delayed

Skin contact	Adverse symptoms may include the following: irritation, redness, dryness, cracking.
Eye Contact	There may be irritation and redness. The eyes may water profusely.
Ingestion	There may be soreness and redness of the mouth and throat.
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest. Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo
Delayed/ Immediate Effects	Immediate effects can be expected after short- -term exposure.

4.5. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5: FIRE-Fighting MEASURES

5.1 Extinguishing Media

Extinguishing Media	Use dry chemical, CO₂, water spray (fog) or
	foam.
	Do not use: water jet, Carbon dioxide, formati-
	on of phosgene.

5.2. Special hazards arising from the substance or mixture

Exposure hazards	In combustion emits toxic fumes.
Hazards from the substance or mixture	Data not known.

Hazardous thermal decomposition products	Decomposition products may include the follo-
	wing materials:
	Carbon oxides, nitrogen oxides and sulfur oxi-
	des

5.3 Advice for fire-fighters

Advice for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed contai-	
	ners cool.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedurs

Personal precautions	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel fromentering. Do not touch or walk through spilt material. Shut off all ignition sources.

For non-emergency personnel	No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

6.2. Environmental precautions

Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and se-
	wers.
	Inform the relevant authorities if the product
	has caused environmental pollution (sewers,
	waterways, soil or air).
	Do not discharge into waterways such as
	drains, lakes, rivers, ocean.
	Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Small spill	Stop leak if without risk.		
	Move containers from spill area.		
	Use spark-proof tools and explosion-proof		
	equipment.		
	Dilute with water and mop up if water-soluble.		
	Alternatively, or if water-insoluble, absorb with		
	an inert dry material and place in an appropria-		
	te waste disposal container.		
	Dispose of via a licensed waste disposal con-		
	tractor.		
Large spill	Stop leak if without risk.		
	Move containers from spill area.		
	Use spark-proof tools and explosion-proof		
	equipment.		
	Approach the release from upwind.		
	Prevent entry into sewers, water courses, base-		
	ments or confined areas.		

Large spill cont.	Wash spillages into an effluent treatment plant
	or proceed as follows.
	Contain and collect spillage with noncombusti-
	ble, absorbent material e.g. sand, earth, ver-
	miculite or diatomaceous earth and place in
	container for disposal according to local regula-
	tions.
	Dispose of via a licensed waste disposal con-
	tractor.
	Contaminated absorbent material may pose the
	same hazard as the spilt product.

6.4. Reference to other sections

Reference to other sections	See Section 1 for emergency contact informati-
	on.
	See Section 8 for information on appropriate
	personal protective equipment.
	See Section 13 for additional waste treatment
	information.

SECTION 7: HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handeling

Handling requirements	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area Do not handle in a confined space.	
	Avoid the formation or spread of mists in the air.	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wearappropriate respirator when ventilation is inadequate.	

Protective measures cont.	Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Temperature	Store between the following temperatures: 13 to 27°C (55.4 to 80.6°F).	
Storage conditions: Exposure	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink.	
Storage conditions: Dangerous reaction	Eliminate all ignition sources. Separate from oxidizing materials.	
Storage conditions: Packaging and Labeling	Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers.	
Storage conditions: Regulations	Store in accordance with local regulations.	

Seveso II Directive - Reporting thresholds (in tonnes)

		Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b C7b: Highly flammable (R11)	No Data	No Data

7.3. Specific end use(s)

Specific end use(s)	UV-light Gel for Nail Modeling.
opcomo ena acción	10 v light corror real modeling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Hazardous ingredients

8.1. Workplace Exposure limits

Exposure Limits	No data available.
-----------------	--------------------

8.1. DNEL/PNEC Values

DNEL/PNEC	No data available.

 TN

NAILPERFECT PROFESSIONAL SYSTEMS

8.2. Exposure controls

Engineering measures	Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.
Respiratory protection	Self-contained breathing apparatus must be available in case of emergency. ALWAYS use protective mask.
Hand protection	ALWAYS use rotective gloves.
Eye protection	ALWAYS use safety glasses. Ensure eye bath is to hand.
Protection of face	Use Protective maks
General Theft Protection	Keep the products locked up when not in use to prevent theft. Keep out of reach of children.

EXPLANATORY DESCRIPTION

General Hygiene Measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing.
	Ensure that eyewash stations and safety showers are close to the workstation location.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

NAILPERFECT PROFESSIONAL SYSTEMS

Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Respiratory protection	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

State	Liquid
Colour	Various Colors
Odor	Characteristic odor.
Flash point°C	>150
Upper/lower flammability or explosive limits	Not available.
Flammablity	Flammable.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Explosion hazard	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available
Viscosity	Viscous liquid

9.2. Other information

Other information	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1.Reactivity

Reactivity	Stable under recommended transport or stora-
	ge conditions.

10.2. Chemical stability

Chemical stability	Stable under normal conditions. Stable at room
	temperature.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Direct sunlight and UV light. Effect: Product
	Hardens

10.5. Incompatible materials

Materials to avoid	Strong oxidizing agents.
	Strong acids.

10.6. Hazardous decomposition products

Reactivity	In combustion emits toxic fumes.
------------	----------------------------------

SECTION 11: TOXICOLOGICAL INFORMATION

11.1..Information on toxicological effects

Hazardous ingredients

Aliphatic Urethane Acrylates

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Ethylphenyl(2,4,6-trimethylbenzoyl)phosphinate

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	Based on the results of the available studies, ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate is not required to be classified for its acute toxicity potential according to 67/548/EEC and CLP/EU-GHS requirements. (European Chemical Agency)
Repeated Exposure Toxicity	Tables 3.9.2 and 3.9.3 of Regulation 1272/2008 (CLP regulation) that require the substance to be classified as a Catergory 1 or 2 toxicant, so based on the results of the study the test material does not require classifiaction for this end point. (European Chemical Agency)

Polyethylene glycol200dimethacrylate

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Silica Dimethyl Silylate

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Isopropylidenediphenyl Bisoxyhydroxypropyl Methacrylate

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Polyester Resin

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Ethylhexyl Acrylate

Carcinogenicity	GHS classification (GHS UN rev.4, 2011) iden-
-	tical to REGULATION (EC) No 1272/2008: no
	classification required (European Chemical Agency)
Acute Toxicity	2-Ethylhexyl acrylate is of low toxicity after a single ingestion and virtually nontoxic after a single skin contact. The inhalation of a highly saturated vapour-air-mixture represents an unlikely acute hazard. (European Chemical Agency)
Repeated Exposure Toxicity	GHS classification (GHS UN rev.4, 2011) identical to REGULATION (EC) No 1272/2008. (European Chemical Agency)

BHT

DITI	
Carcinogenicity	no adverse effect observed (European Chemical Agency)
Acute Toxicity	Since the oral LD50 in rats is greater than 6000 mg/kg bw and the dermal LD50 is greater than 2000 mg/kg bw, the substance is not classified for acute toxicity in accordance to CLP Regulation. (European Chemical Agency)
Repeated Exposure Toxicity	substance is not classified as "Specific target organ toxicity — repeated exposure (European Chemical Agency)

P-Hydroxyanisole

Carcinogenicity	Carcinogenicity: via oral route (EU Risk Assessment Report for MMA (2002); (European Chemical Agency)
Acute Toxicity	Oral route: PMP is officially classified as harmful if swallowed (acute oral toxicity category 4, H302: Harmful if swallowed) according to CLP Regulation (EC) n° 1272/2008 Annex VI table 3. Inhalation: Since PMP particle size is higher than 100 µm, no study by inhalation route is required. Dermal route: Based on the dermal LD50 in rats greater than 2000 mg/kg bw, PMP is not classified for dermal acute toxicity according to CLP Regulation (EC) n° 1272/2008. (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Modified Polysiloxane

Carcinogenicity	No data (European Chemical Agency)
Acute Toxicity	No data (European Chemical Agency)
Repeated Exposure Toxicity	No data (European Chemical Agency)

Hydroquinone

Carcinogenicity	Index No. 604-005-00-4
Acute Toxicity	Index No. 604-005-00-4
Repeated Exposure Toxicity	(EC) 2013/344 Annex III/14

Relevant effects for mixture

Effect	Route	Basis
Ittitation	OPT	Hazardous calculated

11.2.Symptoms / routes of exposure

Ckin contact	There may be irritation and radness at the site
Skin contact	There may be irritation and redness at the site
	of contact. Cracking.
Eye contact	There may be irritation and redness.
	The eyes may water profusely
Ingestion	There may be soreness or redness of the
	mouth and throat.
Inhalation	Adverse symptoms may include the following:
	nausea or vomiting, headache, drowsiness/fati-
	gue, dizziness/vertigo
Delayed / immediate effects: General	Once sensitized, a severe allergic reaction may
	occur when subsequently exposed to very low
	levels. Prolonged or repeated contact can defat
	the skin and lead to irritation, cracking and/or
	dermatitis.
Delayed / immediate effects: Carcinogenicity	No known significant effects or critical hazards.
Delayed / immediate effects: Mutagenicity	No known significant effects or critical hazards.
Delayed / immediate effects: Teratogenicity	No known significant effects or critical hazards.
Delayed / immediate effects: Developmental effects	No known significant effects or critical hazards.
Delayed / immediate effects: Fertility effects	No known significant effects or critical hazards.

SECTION 12: ECOLOGICAL INFORMATION

12.1.Toxicity

Biotocidity data, if relevant, can be found under the European Chemical Agency's website www.echa.eu - cas number or inci name.

12.2. Persistence and degradability

Persistence and degradability	Biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential data, if relevant, can be found under the European Chemical Agency's website www.echa.eu - cas number or inci name.

12.4. Mobility in soil

Soil/water partition coefficient (KOC)	No Data Available
Mobility	No Data Available

12.5. Results of PBT and vPvB assessment

PBT identification	This product is not identified as a PBT substan-
	ce.
vPvB identification	This product is not identified as a vPvB substan-
	ce.

12.6. Other adverse effects

Other adverse effects	No Bioaccumulation.
-----------------------	---------------------

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Disposal operations	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not bedisposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	The classification of the product may meet the criteria for a hazardous waste.
Hazardous waste	The generation of waste should be avoided or minimised wherever possible. Wastepackaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should betaken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA
14.1	None	None	None	None
UN number				
14.2	None	None	None	None
UN proper ship-				
ping name				
14.3	None	None	None	None
Transport ha-				
zard class(es)				
14.4	None	None	None	None
Packing				
group				
14.5	No.	No.	No.	No.
Environmental				
hazards				
Additional information	-	-	-	-
IIIIalialia	l			

114.6. Special precautions for user

Special precautions	Transport within user's premises: always trans-
	port in closed containers that are upright and
	secure. Ensure that persons transporting the
	product know what to do in the event of an ac-
	cident or spillage.

114.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Special precautions	Transport within user's premises: always trans-
	port in closed containers that are upright and
	secure. Ensure that persons transporting the
	product know what to do in the event of an ac-
	cident or spillage.

SECTION 15: TRANSPORT INFORMATION

15.1. Safety, health and environmental regulation/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation

Annex XIV	None of the components are listed.
Substances of very high concern	None of the components are listed.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Other EU regulations	All components are listed or exempted.
Europe inventory	
Seveso II Directive	Not applicable.
Danger criteria : Category	Not applicable.
15.2 Chemical Safety	Unknown
Assessment	

ГΜ

NAILPERFECT PROFESSIONAL SYSTEMS

SECTION 16: OTHER INFORMATION

Other information:

Other information	This safety data sheet is prepared in accordance with Regulation (EC) No 453/2010 * Indicates text in the SDS which has changed since the last revision
Phrases used in s.2 and 3	H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H361f: Suspected of damaging fertility. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects.

Abbreviations and	ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging
	Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard state-
	ment
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumula-
	tive

NAILPERFECT PROFESSIONAL SYSTEMS

Aquatic Chronic 3, H412 Eye Irrit. 2, H319	LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION -
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H336	Category 2 FLAMMABLE LIQUIDS - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SIN-GLE EXPOSURE) [Narcotic effects] - Category 3
Phrases used in s.2 and 3	EUH066: Repeated exposure may cause skin dryness or cracking. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects. R10: Flammable. R11: Highly flammable R36/38: Irritating to eyes and skin.
Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3,	Calculation method Calculation method
H336 (Narcotic effects)	Calculation method
Aquatic Chronic 3, H412	Calculation method

Legal disclaimer	The above information is believed to be correct
	but does not purport to be all inclusive and shall
	be used only as a guide. This company shall
	not be held liable for any damage resulting from
	handling or from contact with the above pro-
	duct.

The contents and format of this SDS are in accordance with REgulation (EC) No. 1907/2006, 1272/2008 and Regulation (EU) No. 2015/830.

DISCLAIMER OF LIABILITY:

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methos of handling, storage, use or disposal of the product are beyond our control and may be behound our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Abbriviations and acronyms

COMMON ABRIVIATIONS WHICH MAY OR MAY NOT BE USED IN THIS MSDS SHEET.

°C	Degrees in Centigrade
°F	Degrees in Farenheit
ADR	Accord European sur le transport des marchan- dises dangereuse par Route (European Agree- ment concerning the International
ATE	Acute Toxicity Estimate
CAS Number	Chemical Abstract Service - Registry number. Identification number for a specific substance.
CLP	Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC Number	Enzyme Commission Number. Numerical classification for enzymes. Specific number.
EC25	Effect Concentration e.g. EC25 - is at 25%
IMDG	International Maritime Code for Dangerous Goods.
IATA	Internatinal Air Transport Association
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LC50	The concentration of a material in air which, on the basis of laboratory tests, is expected to kill 50% of a group
LOEC	Lowest concentration where an effect has been observed in chronic ecotoxicity studies

COMMON ABRIVIATIONS WHICH MAY OR MAY NOT BE USED IN THIS MSDS SHEET.

Log Pow	A product's ability to bioaccumulate through the food chain
mg/L	Miligrams per Liter
MSDS	Material Safety Data Sheet
N/E	Not Explored - No data available.
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
RRN	REACH Registration Number
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No Effect Concentration
SDS	Safety Data Sheet
SVHC	Substance of Very High Concern
EUH statement	CLP-specific Hazard statement
vPvB	Very Persistent and Very Bioaccumulative
Eye Irrit. 2, H319	Calculation method
I Skin Sens 1 H317 STOT SF 3	l Calculation method

Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317 STOT SE 3,	Calculation method
H336 (Narcotic effects)	Calculation method
Aquatic Chronic 3, H412	Calculation method

The following page contains explanation of abriviative warnings which may or may not be of concern to this SDS. See section 2 and 3 to determine if these warnings are applicable to this product!

TN

NAILPERFECT

PROFESSIONAL SYSTEMS

COMMON WARNINGS WHICH MAY OR MAY NOT BE USED IN THIS MSDS SHEET: See section 2 and 3 which are applicable to this product.	
H220:	Extremely flammable gas
H225:	Highly flammable liquid and vapour
H226:	Flammable liquid and vapour
H241:	Heating may cause a fire or explosion
H242:	Heating may cause a fire
H302:	Harmful if swallowed.
H312:	Harmful in contact with skin or if inhaled
H313:	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315:	Causes skin irritation.
H316:	Causes mild skin irritation
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H319:	Causes serious eye irritation.
H330	Fatal if inhaled
H332:	Harmful if inhaled
H334:	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335:	May cause respiratory irritation.
H336:	May cause respiratory irritation
H340:	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H341:	Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H350:	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H351:	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H361f:	Suspected of damaging fertility.
H370:	Causes damage to organs (or state all organs affected, if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

TN

NAILPERFECT PROFESSIONAL SYSTEMS

	NHICH MAY OR MAY NOT BE USED IN THIS MSDS nd 3 which are applicable to this product.
Acute Tox. 1	ACUTE TOXIDITY - Category 1 Falal if Inhaled
Acute Tox. 2	ACUTE TOXIDITY - Category 2 Falal if Inhaled
Acute Tox. 3	ACUTE TOXIDITY - Category 3 Toxic if inhaled
Acute Tox. 4	ACUTE TOXIDITY - Category 4 Harmful if inhaled
Aq.Chron. 1	LONG-TERM AQUATIC HAZARD - Category 1
Aq.Chron. 2	LONG-TERM AQUATIC HAZARD - Category 2
Aq.Chron. 3	LONG-TERM AQUATIC HAZARD - Category 3
Carc. 1A	CARCINOGEN - Category 1 Known to have carcinogen potential for humans
Carc. 1B	CARCINOGEN - Category 1 Presumed to have carcinogen potential for humans
Carc. 2	CARCINOGEN - Category 2 Limited evidence from studies
Eye Dam. 1	SERIOUS EYE DAMAGE - Category 1 Irreversable effects on the eye
Eye Irrit. 2	SERIOUS EYE IRRITATION - Category 2 Irritating to eyes. Fully reversable normally in 21 days or less.
Eye Irrit. 2B	EYE IRRITATION - Category 2B Mildly irritating to eyes. Fully reversable in 7 days.
Flam. Liq. 1	FLAMMABLE LIQUIDS - Category 1 Flashpoint <23°C (73.4°F) and initial boiling point <35°C (95°F)
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2 (Flashpoint <23°C (73.4°F) and initial boiling point >35°C (95°F))
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 1 Flashpoint >23°C (73.4°F) and initial boiling point <60°C (140°F)
Muta. 1A	MUTATION OF CELLS - Category 1 Known to induce heritable mutations in germ

COMMON WARNINGS WHICH MAY OR MAY NOT BE USED IN THIS MSDS	
SHEET: See section 2 and 3 which a	re applicable to this product.
H371:	May cause damage to organs (or state all organs affected, if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H372:	Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H373:	May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
H400:	Very toxic to aquatic life.
H410:	Very toxic to aquatic life with long lasting effects.
H411:	Toxic to aquatic life with long lasting effects
H412:	Harmful to aquatic life with long lasting effects.
H413:	May cause long lasting harmful effects to aquatic life
EUH066:	Repeated exposure may cause skin dryness or cracking.
For Professional Use Only	Shoudl be used by professionally trained personell only. Specific training for this product needed.

NAILPERFECT

PROFESSIONAL SYSTEMS

COMMON WARNINGS WHICH MAY OR MAY NOT BE USED IN THIS MSDS	
SHEET: See section 2 and 3	B which are applicable to this product.
Muta. 1B	MUTATION OF CELLS - Category 1 Regarded as if induce heritable mutations in germ cells of humans
Muta. 1B	MUTATION OF CELLS - Category 2 Causes concern for the possibility of causing heritable mutations in germ cells of humans
Rep. 2	REPRODUCTIVE TOXIDITY - Category 2 Evidence from human studies is limited. May spread through breastfeeding
Resp. Sens. 1A	RESPITORY SENSITIZATION - Category 1 Evidence in Humans that the substance can induce respiratory hypersensitivity
Resp. Sens 1B	RESPITORY SENSITIZATION - Category 1 Suspected that the substance can induce respiratory hypersensitivity
Skin Corr. 1	SKIN CORROSION - Category 1 Irreversable effects on the skin
Skin Corr. 1A	SKIN CORROSION - Category 1A Irreversable effects on the skin in less than 3 minutes exposure
Skin Corr. 1B	SKIN CORROSION - Category 1B Irreversable effects on the skin in 3 minutes - 60 minutes exposure
Skin Irrit. 2	SKIN IRRITATION - Category 2 Causes reversable skin irritation effects. Recovery within 21 days to be expected.
Skin Sens. 1	SKIN SENSITIZATION - Category 1 Causing significant sensitization in humans when on skin
Skin Sens. 1A	SKIN SENSITIZATION - Category 1 Causing significant sensitization in humans when on skin
Skin Sens. 1B	SKIN SENSITIZATION - Category 1 Low to moderate fequency of causing significant sensitization in humans
Skin Sens. 2	SKIN SENSITIZATION - Category 2 Low chance of skin sensitization in humans

COMMON WARNINGS WHICH MAY OR MAY NOT BE USED IN THIS MSDS	
SHEET: See section 2 and 3 which are applicable to this product.	
STOT SE 1	SPECIFIC TARGET ORGAN TOXICITY (SIN-GLE EXPOSURE) - Category 1 Potential to produce significant toxidity in humans following a single exposure.
STOT SE 2	SPECIFIC TARGET ORGAN TOXICITY (SIN-GLE EXPOSURE) - Category 2 Potential to be harmful in human health after a single exposure.
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SIN-GLE EXPOSURE) - Category 3 Potential to cause narcotic effects (dizziness, drowsiness) and respiratory tract irritation (sore throat, caugh). These effects are temporary/not long term.
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (RE- PEATED EXPOSURE) - Category 2 Potential to be harmful in human health after a repeated exposures.

End of safety data sheet